# ultralight

**Creating Panel Connections** 



### Connections



Overlay hinge Exterior folding hinge Concealed hinge Häfele hinges and connectors



flat connection

Fastmount Knob/Handle (metric screw) Knob/Handle (wood screw)





90° connection

Ovvo connector Shelf bracket

Wood screw connection with washer

Countersunk wood screw connection

Inclined wood screw connection

90° connection with dowel pin Long eccentric

Short eccentric Lamello Cabineo



Insert for metric screw (visible)

Insert for metric screw (concealed)

Blind rivet

Würth Coldmelt Technology

Sliding door system

### Tools







rivet gun





cutter





Filled

Edges

#### Accessories



dowel pin





wood screw



**PVA** adhesive



rivet



**PU** adhesive



metric



PC adhesive





**EVA** adhesive







## **Overlay hinge**

#### Overlay hinge used on doors, cupboards, kitchen furniture.


\* The wood screw used must apply grip force between 2 and 8 mm of the shank. \*\* The resistance of the 4.5 mm poplar faces is usually sufficient for standard connections. 6 mm poplar faces are also available for applications that require greater strength, such as large furniture, doors, etc.

#### **ADVANTAGES:**

- ✓ Less stress on the hinge and screws thanks to the lighter weight of the Ultralight panel
- ✓ High screw pull-out resistance
- ✓ Only standard components are required

#### **SUPPLIER:**

Regular supplier







#### Tools



saw



#### **Accessories**



## **Exterior folding hinge**

## Exterior folding hinge for use on both interior and exterior doors.


#### **ADVANTAGES:**


- ✓ Less stress on the hinge and screws thanks to the lighter weight of the Ultralight panel
- ✓ High screw pull-out resistance
- ✓ Only standard components are required

#### SUPPLIER:

Regular supplier











saw



**Accessories** 



wood screw









## **Concealed hinge**

### Concealed hinge used for both exterior and interior doors and cupboards.


#### **ADVANTAGES:**


- ✓ Less stress on the hinge and screws thanks to the lighter weight of the Ultralight panel
- ✓ High screw pull-out resistance
- ✓ Only standard use components are required
- ✓ Concealed hinge

#### **SUPPLIER:**

Regular supplier













#### Accessories



wood screw



## Häfele hinges and connectors

### Hinges and connectors for interior caravan furniture.

#### **HINGE ADVANTAGES:**

- ✓ Lighter than a standard hinge
- ✓ Less stress on the hinge and screws thanks to the lighter weight of the panel
- ✓ High screw pull-out resistance
- ✓ Only standard components are required







#### **CONNECTOR ADVANTAGES:**

- ✓ Reversible connection and exceptionally lightweight
- ✓ High screw pull-out resistance
- ✓ Easy to use with common tools



















### **Fastmount**

The Fastmount connection is perfect for countless uses in panelling, false ceilings, acoustic panels, furniture, upholstery, etc.

\* The website of the supplier indicates the technology necessary for this system.

#### **ADVANTAGES:**


- ✓ Invisible connections
- ✓ Lightweight
- ✓ Reversible
- ✓ Easy to install
- ✓ Wide variety of solutions
- ✓ Suitable for outdoor use
- ✓ Absorbs expansions and contractions

#### **SUPPLIER:**

www.fastmount.com







Tools





## **Knob/Handle (metric screw)**

Knob/handle (wood screw) for handle use.


#### **ADVANTAGES:**

✓ Easily machinable

#### **SUPPLIER:**

Regular supplier









Accessories









## **Knob/Handle (wood screw)**


Knob/handle (wood screw) for handle use.


#### **ADVANTAGES:**

✓ Easily machinable

#### **SUPPLIER:**

Regular supplier





#### Tools





#### Accessories



## **Connection on the same plane**

### Lengthening Ultralight panels.


- $^{*}$  The cutting gear must be central on the edge and 1mm thicker than the XPS.
- \*\* The connecting piece must be twice as thick as the insulation.

#### **ADVANTAGES:**


✓ Lengthens the Ultralight panel surface

#### SUPPLIER:

Regular supplier











Accessories









### **Ovvo connector**

#### Ovvo connector used in furniture.

- \* Requires edging of at least 0.2 mm on the edge.
- \*\* The website of the supplier contains the technical information necessary.


#### **ADVANTAGES:**

- ✓ Connection versatility
- ✓ Connector option for joining parallel planes, at an angle or perpendicular
- ✓ Fixed or reversible connection option

#### **SUPPLIER:**

www.ovvotech.com







#### Tools





#### Accessories



### **Shelf bracket**

#### Shelf bracket connection used for supporting shelves, removable assemblies.


#### **ADVANTAGES:**

- ✓ Component allows reversible shelf support
- ✓ High screw pull-out resistance
- ✓ Option to create removable assemblies
- ✓ Concealed hinge

#### **SUPPLIER:**

www.emuca.es | www.hettich.com | www.wuerth.com





















## **Wood screw connection with washer**

Wood screw connection with washer used for 90° connections in furniture

#### **ADVANTAGES:**

- ✓ Strong mount with pressure base
- ✓ High screw pull-out resistance
- ✓ Standard components only

#### SUPPLIER:

Regular supplier





## Tools



### Accessories





### **Countersunk wood screw connection**


Countersunk wood screw connection used for 90° connections in furniture.


#### **ADVANTAGES:**

- ✓ Strong mount with flush head
- ✓ High screw pull-out resistance
- ✓ Standard components only

#### SUPPLIER:

Regular supplier







Accessories













### **Inclined wood screw connection**


Inclined wood screw connection used for 90° connections in furniture.

#### **ADVANTAGES:**

- ✓ Strong mount with flush head.
- ✓ High screw pull-out resistance

#### SUPPLIER:

Regular supplier







### Tools



#### Accessories





## 90° connection with dowel pin

### 90° connection with dowel pin used in furniture.

\* The dowel pin must have a diameter of 1 mm or be larger than the XPS and the drilling must be central on the edge.

#### **ADVANTAGES:**

- ✓ Concealed anchoring
- ✓ Standard components only

#### **SUPPLIER:**

Regular supplier



#### Tools





#### Accessories



dowel pin









## **Long eccentric**

## Long 90° eccentric connection for drawers, removable assemblies.


- \* No edging required for use.
- \*\* For a better connection, filled edge recommended on eccentric side.

#### **ADVANTAGES:**

- ✓ Reversible connection
- ✓ High screw pull-out resistance

#### **SUPPLIER:**

www.emuca.es | www.hettich.com | www.wuerth.com







#### Tools



saw



utter



### **Short eccentric**


## Short 90° eccentric connection for drawers, removable assemblies.

#### **ADVANTAGES:**

- ✓ Reversible connection
- ✓ High screw pull-out resistance

#### **SUPPLIER:**

www.emuca.es | www.hettich.com | www.wuerth.com











saw



cutter









### **Lamello Cabineo**

## Lamello Cabineo 90° connection for drawers, removable assemblies.


\* The website of the supplier contains the technical information necessary.

#### **ADVANTAGES:**


- ✓ Reversible connection
- ✓ High screw pull-out resistance

#### **SUPPLIER:**

www.lamello.com







#### Tools



saw





## Insert for metric screw (visible)


Insert for metric screw (visible) for furniture feet, connections on the same plane with metric screws.

#### **ADVANTAGES:**

✓ Insert for connection with metric screws and bolts to affix all sorts of components, furniture feet, other panels on the same plane, extra thicknesses

#### **SUPPLIER:**

Regular supplier









saw









## Insert for metric screw (concealed)


Insert for metric screw (concealed) for furniture feet, connections on the same plane with metric screws.


#### **ADVANTAGES:**

✓ Insert for connection with metric screws and bolts to affix all sorts of components, furniture feet, other panels on the same plane, extra thicknesses

#### SUPPLIER:

Regular supplier







#### Tools



saw



### **Blind rivet**

## Blind rivet for furniture feet, connections on the same plane with metric screws.


\* The drill diameter must be that which is defined by the rivet manufacturers.


#### **ADVANTAGES:**

✓ Permanent connection

#### **SUPPLIER:**

Regular supplier







saw





rivet gur







## **Würth Coldmelt Technology**

### Würth Coldmelt Technology for mounting screws and fittings on lightweight panels.

\* The website of the supplier indicates the technology necessary for this system.

#### **ADVANTAGES:**

- ✓ Technology for adhesive-free insertion of adjustable plastic anchors in lightweight panels
- ✓ For mounting screws and fittings

#### **SUPPLIER:**

www.wuerth.com







#### Tools



## **Sliding door system**

### Sliding cupboard door system


\* The wood screw used must apply grip force between 2 and 8 mm of the shank.

#### **ADVANTAGES:**

- ✓ Easier to move due to lightweight Ultralight panel
- ✓ Less wear on the fitting due to lightweight Ultralight panel
- ✓ High screw pull-out resistance


#### **SUPPLIER:**

www.gedotec-beschläge.de | www.ducasseindustrial.com













Accessories









### **Filled**

#### Reinforced edges.

\* The cutting gear must be central on the edge and 1 mm thicker than the XPS.

#### **ADVANTAGES:**


- ✓ Gives plywood characteristics to the edge
- ✓ Can be machined like a solid plywood panel
- ✓ High screw pull-out resistance

#### **SUPPLIER:**

Regular supplier







### Tools





### Accessories





## **Edges**

### **Edge protection.**

- \* The right adhesive for the type of edging must be used.
- \*\* Due to the lower density of Ultralight when compared with conventional plywood panels, it may be necessary to reduce the roller pressure during the edging process.

#### **ADVANTAGES:**

✓ Ultralight panels can be edged with all types of edges, PVC, ABS, veneer and melamine

#### **SUPPLIER:**

Regular supplier





Tools



Accessories



edge



**PVA** adhesive





